

What is claimed is:

1. A walker for rehabilitant, comprising a base provided at predetermined positions with caster holders, a handlebar assembly connected to an upright hollow column provided on a top of said base, a suspension frame connected to an upper end of said hollow column, and a leg separator connected to a rear center of said base; said caster holders having casters connected thereto to facilitate sliding of said walker in different directions;

said walker being characterized in that said leg separator includes a perpendicular leg separating board, and an L-shaped fixing bar, which has a horizontal section connected at a front end to said base and a vertical section connected to a front end of said leg separating board; that said fixing bar is provided at the front end of said horizontal section with two first pin holes, and at the vertical section with at least two second pin holes; that said base is provided at the rear center with a lengthwise channel, in which said horizontal section of said fixing bar is located in place using insertion pins extended through said two first pin holes; that said leg separating board is provided at the front end

with a vertical groove, with which said vertical section of said fixing bar is engaged using insertion pins extended through said at least two second pin holes; and that said leg separating board is provided along said front end with at least three through holes corresponding to different ones of said second pin holes on said fixing bar to allow adjustment of said leg separating board to different heights relative to said fixing bar.

10

2. The walker for rehabilitant as claimed in claim 1, wherein said base is provided above each said caster holder with a pivotally turnable direction control member, which has a front part shaped for enclosing two lateral sides of said caster holder when said direction control member is in a downward turned position, and said direction control member in said downward turned position being able to limit said caster holder, and accordingly said caster connected thereto, to move forward or backward only.

15

20